## Frequently Asked Question



## How to set security (user ID and password) on the EntryData object directly without having a different login button?

Α

Create two different objects with three different functions included. Object #1 has "EntryData" and "Visible" functions while object #2 has "Touch" function which would act as a login button. And then group these two different objects into one single object.

M CIMON	
File View Work Help	
i 📂 🔀 🥔   🖨   😒   🔗 🛞   🖬 🥖 🖧 🖀 🗎 🗟 🚯 🛍   🥥	
MAIN	
1. Security feature pops up before you enter numeric value.	User Log In User ID cimon Password OK Cancel





1. Register one analog tag for "EntryData" and another digital tag for "Visible" functions.

A DATABASE [Test.dbx]								
🛯 🎝 🖨 🖻 😧								
······ 🖳 Test	Name		Туре	I/O device	I/O Address	Initial V	Additional	Description
	<b>à</b> AA		Analog Tag			0		
	🛋 VIS	IBLE	Digital Tag			0		
		Edit Tag		Ganard			X	
		Group		Genera	Advanced			
		Name	AA		🔘 Real Tag	Virtua	l Tag	
			<ul> <li>Group</li> <li>Digital</li> <li>Analog</li> </ul>	I/C I/C	) Device		-	
		Des	String	S	ave last status v	vhen closing	<b>^</b>	
		003.			/rite initial value ssign as Alarm Ta reate data for R	in I/O Device ag eport	=	
	•			R	eset accumulate	d value manu	ally 👻	+
			Previous	Next	Ok	Ca	ncel	

2. Create two "Tag Value" objects.

🔄 [MAIN.PGX] ×	
[MAIN.PGX]	
????	????



3. For the Object 1, register "Visible" function with the digital tag attached.

	• 0000	· · · · · · · · · · · · · · · · · · ·
????	<u></u>	
Object Config		23
Name Object1	Visible	
Config		
Style		
	Tagpame VISIBLE	
	Condition	
	◉ On ◯ Off	
V-Slider H-Slider		
Color Rotate		
Touch Touch EntryData		
Tag Value		
	Ok Cancel	

4. For the Object 1, register also "EntryData" function with the analog tag.

Object Config	
Name Object1	Action Touch Shape Tooltip Security P
Type Tag Value	Action Numeric Vice Double Click
Style	
Visible 🔲 Blink	Tagname 🗛
V-Size H-Size	Min Value ?
V-Move H-Move	Scale/Offset Scale: 1
V-Fill H-Fill	Style Offset: 0
V-Slider H-Slider	Window Style 1
Color Rotate	Title
Touch 🔽 EntryData	Comment
Tag Value	
	Ok Cancel



Frequently Asked Question

5. For the Object 1, go to "Security" tap and enter 50 for the "Security Level." Security level as 1 has the highest authorization whereas security level as 100 has the lowest authorization.

Object Config	
Name Object1	Action Touch Shape Tooltip Security P
Type Tag Value	
Config	
✓ Style	
Visible 🔲 Blink	
V-Size H-Size	Security Level 50
V-Move H-Move	
V-Fill H-Fill	
V-Slider H-Slider	
Color Rotate	
Touch Touch	
✓ Tag Value	
	Ok Cancel

6. Set up a Security feature.

???	?	?'	???	Security Propertie	is			Σ
	•			User ID	Cimon		Level	30 🚔 (1 - 100
· · · · · · · · · · · · ·		· · · · · · · · ·	· · · · · · · · · · · · · ·	Name	Cimon			Password
ecurity Configurati	on			Log In Action	Visible=1			Password as
Base Security Level	100	(1-100)		Log Out Action				
ID	Name	Level	Log In Action	User Menu	Use			
age Cimon	Cimon	30	Visible=1	User Limit Time	🔲 Use	1970-01-01		
				User Group				
				<b>A</b>		В	C	D
				E		F	G	ΠH
				I		ı	К	E L
				M		N	0	P
								Ok Cancel
New User	Edit	Delete						

Ex) User ID – Cimon, Level – 30, Password – 1, Log In Action: Visible = 1



7. For the Object 2, register "Touch" function which would act as a login button. Use "Command Expression" for the Action Script "LogIn()"

Object Config	X
Name Object2	Action Script Touch Shape Tooltip Security
Type Tag Value Config Style Visible Blink V-Size H-Size V-Move H-Move V-Fill H-Fill V-Slider K-Slider Color Rotate Touch EntryData	Action Command Expression Mouse Right Button Command - Down Command - Up LogIn()
	Ok Cancel

## 8. For the object 2, make sure to mark "Use User Group."

Object Config	
Name Object2	Action Script Touch Shape Tooltip Security
Type Tag Value	
Style	
Visible Blink	
V-Size H-Size	Security Level 100
V-Move H-Move	Select User Group A GROUP
V-Fill H-Fill	Use User Group
V-Slider H-Slider	
Color Rotate	
Touch EntryData	
Tag Value	
	Ok Cancel



9. Now that you have two different objects with three different functions, combine these two into one single object by grouping.

[MAIN.PGX] ×			e	
[MAIN.PGX]		17777	Cut	Ctrl+X
			Сору	Ctrl+C
	2222	· · · · · · · · · · · · ·	Paste	Ctrl+V
	: 12222		Paste(Cursor)	
			Paste(Same Po	sition)
			Object Config(	W)
			Group	
			UnGroup	
			ReGroup	
			Arrange	۶.
			Rotate	→
			Flip(M)	+
			Bring To Front	
			Send To Back	
			Send TO Back	
			Object	

## 10. Activate CimonX.

ᢔ CIMON	
File View Work Help	
i 🛍 📓 🖉 🕞 😒 🛛 🔗 🛞 🖬 🗖 🥖	- 22 🗟 🖪 🔂 🕢
r 📮 MAIN	
0	User Log In User ID cimon Password • OK Cancel